


Pneumatic Quick Release Couplings

P320 Series - European Standard




Features


- Standard: European Standard
- Sizes 1/4" - 3/8"
- Nominal flow diameter: 7.6mm
- Working pressure: 1.6 Mpa
- Carbon steel
- NBR sealing
- Corrosion resistant - CR3
- Interchange: Cejn 320, Rectus 25KA and 26KA




Part No.	O/L	D	Hex 1	A	T	d
P320-F-04GM	63.2	23.3	20	13	1/4	7.8
P320-F-06GM	61.2	23.3	20	13	3/8	11.3




Part No.	O/L	C	Hex 2	A	T	d
P320-M-04GM	39.5	20.5	17	13	1/4	7.5
P320-M-06GM	40.5	22	14	12.5	3/8	7.5




Part No.	O/L	D	Hex 1	A	T	d
P320-F-04GF	60.2	23.3	20	13	1/4	14
P320-F-06GF	60.2	23.3	22	12	3/8	14



Part No.	O/L	C	Hex 1	A	T	d
P320-M-04GF	36.5	20.5	17	13	1/4	7.5
P320-M-06GF	36.5	20.5	19	13	3/8	7.5



Part No.	O/L	D	Hex 1	A	T	d
P320-F-07B	67.7	23.3	20	20	7	4
P320-F-09B	72.7	23.3	20	25	9	5.5
P320-F-11B	72.7	23.3	20	25	11	7.5



Part No.	O/L	C	Hex 1	A	T	d
P320-M-07B	43	20.5	15	20	7	7.5
P320-M-09B	48	20.5	15	25	9	7.5
P320-M-11B	48	20.5	15	25	11	7.5