


Pneumatic Quick Release Couplings

P550 Series ISO 6150B & A-A-59439 11 mm


Features




- Standard: ISO 6150B - High Flow
- Sizes 1/2" & 3/4"
- Nominal flow diameter: 11 mm
- Carbon Steel
- NBR sealing
- Corrosion resistant - CR3
- Working pressure 1.6 Mpa
- Interchange: Cejn 550




Part No.	O/L	D	Hex 1	A	T	d
P550-F-04GM	79.9	28.1	24	16	1/2	14
P550-F-06GM	81.8	28.1	27	18	3/4	18




Part No.	O/L	C	Hex 1	A	T	d
P550-M-04GM	59.5	35	22	16	1/2	11
P550-M-06GM	63	35	27	18	3/4	18




Part No.	O/L	D	Hex 1	A	T	d
P550-F-04GF	78.3	28.1	27	16	1/2	17.9
P550-F-06GF	79.8	28.1	32	18	3/4	17.9



Part No.	O/L	C	Hex 1	A	T	d
P550-M-04GF	55	35	27	16	1/2	11
P550-M-06GF	57	35	32	18	3/4	11



Part No.	O/L	D	Hex 1	A	T	d
P550-F-10B	96.3	28.1	24	30	15	10
P550-F-15B	96.3	28.1	24	30	20.5	15



Part No.	O/L	C	Hex 1	A	T	d
P550-M-10B	68	35	23	30	15	10
P550-M-15B	68	35	23	30	20.3	15